

ActiView 322

Product Specifications

INTERACTIVE TOOL

In the ActivClassroom, we show much more than tell. Bring any object or document to the ActiView 322 Visual Presenter, and the whole class can share in the finer details. Capture 3D objects for interactive show and tell, class work for review sessions, art, texts, flora, fauna, anything—ActiView puts it on view, on the ActivBoard for all to see.

GENERAL SPECIFICATIONS

ActivInspire Integration	Full integration with ActivInspire allowing operation of the presenter from the software (Professional only)
Output Resolution	XGA (1024 x 768); SXGA (1280 x 1024), WXGA (1280 x 800)
Frame Rate	20 fps
Zoom Capacity	6X Mechanical Zoom and 6X Digital Zoom
Capture Area	350mm x 280MM (14in x 11in)
Lamp Type	Cold cathode lamp (light source is separate from camera)
Lamp Life	Up to 20,000 hours
Number of Lamps	One light on gooseneck
Power Supply	Built-in; 100-240 VAC, auto switching
VGA Pass Through Max Display Mode	Active pass-through, up to UXGA 60 Hz; VGA In and VGA Out
USB	USB 2.0 High Speed (up to 480 Mbps)
Composite Video Out	RCA Jack
Operation Functions	Auto Tune (single button to adjust for best possible image); Auto Exposure; Auto White Balance; Auto Focus; Photo/Text Mode (choose photo/grayscale/text mode); Image Mode (choose normal/35mm slide/microscope/negative film)
Internal Memory	120 JPEG Images
Image Capture	Capture images to internal memory or to the computer via USB connection; Picture by Picture, Freeze
Slide Show	FastSlide™ Technology to automatically or manually playback saved images; 5 slide show transition effects: shutter/right/down/slide/open
Image Rotation	Full screen image rotation from 90, 180 to 270 degrees
Pan	Automatically zoom from full page to separate quadrants



Continued on Next Page

Page 1

©2009 Promethean Ltd. All Rights Reserved. ActiView is a trademark of Promethean Ltd. Any third-party product and company names are mentioned for identification purposes only and may be trademarks of their respective owners. All dimensions +/- 5mm (0.2in). All weights +/- 0.9kg (2lb). www.prometheanworld.com Product Specifications are subject to change without notice. 12/09

GENERAL SPECIFICATIONS (CONTINUED)

Security	Auto Erase Mode (option to automatically erase internal memory during power down); Kensington lock slot available; screw holes provide to mount to a cart
Certifications/Compliance	FCC-EMI, cUL, CE-EMC, CE-LVD, RoHS, and WEEE
Weight	2.3kg (5lbs)
Dimension	460cm x 220cm x 400cm (18.1in x 5.5in x 15.7in) (LxWxH)
Languages	Chinese (Traditional), Dutch, English, Finnish, French, German, Polish, Russian and Spanish
Packed Contents List	Power cable, VGA cable, USB cable, Composite video cable, microscope adapters, remote control, (US/UK/EMEA Power leads) CD and User Manual

RECOMMENDED COMPUTER REQUIREMENTS

Operating Systems	Windows XP 32bit, Vista 32 and 64bit; Macintosh OS 10.4, 10.5; Linux Ubuntu 8:10 and 9.04
--------------------------	---

MINIMUM SYSTEM REQUIREMENTS FOR USE WITH ACTIVINSPIRE AND/OR ACTIVBOARD

Operating Systems	Windows XP SP2 and above (XP/Vista/7) Mac OSX 10.4.11 – 10.6.1 (Tiger/Leopard/Snow Leopard) Linux Ubuntu 8.04, 8.10, 9.04, 9.10; Mandriva
PC	Pentium 4 – 1 GHz processor (800MHz for Vista), 512 MB of RAM, 1024x768 resolution, 1.5 GB of Free Disk space
Mac	Intel Processors (Universal Binary), 512 MB of RAM, 1024x768 resolution, 3.0 GB of Free Disk Space

WARRANTY AND SUPPORT

ActiView 322	Three-Year Warranty (Return-To-Base) 90-Day Telephone Support KnowledgeBase: www.prometheankb.com
---------------------	---